



Model: *Jade Counter* *JC2 & JC3 Export*

Project:

Location:

Item #:

Quantity:

Variant	Op Temp & Storage
HJC2	+1/+4°C - General Produce
MJC2	-2/+2°C - Meat Storage
LJC2	-18/-22°C - Frozen Food
HJC3	+1/+4°C - General Produce
MJC3	-2/+2°C - Meat Storage
LJC3	-18/-22°C - Frozen Food

Optional Features

- Drawer banks (2 or 3)
- Raised Panholder
- Screw on splash-back
- Helicoil cable
- Shelves/trayslides
- Reverse unit

Key Features

- 304 stainless steel interior and exterior finish for hygiene and durability
- CoolSmart intelligent controller offering 15% energy savings, enhanced performance; energy efficient economy mode ensuring effective temperature control for excellent food safety and improved defrost functionality for increased cabinet efficiency
- CoolSmart controller is designed for easy operation and features clear digital display
- High performance, efficient commercial refrigeration system for increased energy efficiency and quieter improved performance
- Efficient and effective performance in 43°C ambient environments
- Environmentally friendly 75mm ODP Zero polyurethane foam injected insulation for excellent thermal efficiency
- Accommodate nylon coated 1/1 gastronorm wire shelves or pairs of trayslides
- Self closing lockable doors with 90° dwell and fitted with easy to clean and replace magnetic balloon gaskets
- 128mm heavy duty, non marking front and rear swivel and break castors for easy positioning and maneuverability
- Removable refrigeration cassette systems for easy servicing and maintenance
- Removable internal fittings including racking and shelf supports for easy cleaning and hygiene
- Designed and built to ISO9001-2000 Quality Management Standards
- HACCP compliant





2-drawer option



Raised Panholder option

Dimensions

	HJC2	MJC2	LJC2	HJC3	MJC3	LJC3
External (mm):	H865 W1420 D659	H865 W1420 D659	H865 W1420 D659	H865 W1885 D659	H865 W1885 D659	H865 W1185 D659
Internal (mm): (width per section)	H915 W390 D560	H600 W390 D560	H600 W390 D560	H600 W390 D560	H600 W390 D560	H600 W390 D560
Door Opening (mm):	D1090	D1090	D1090	D1090	D1090	D1090
Packed (max):	H965 W1520 D750	H965 W1520 D750	H965 W1520 D750	H965 W1985 D750	H965 W1985 D750	H965 W1985 D750
Weight: Add 5kg per product for packing	115kg	115kg	115kg	140kg	140kg	140kg

Important Information

	HJC2	MJC2	LJC2	HJC3	MJC3	LJC3
Capacity: cu.ft/litres	12.5 / 354	12.5 / 354	12.5 / 354	18 / 510	18 / 510	18 / 510
Construction: Exterior Interior Door	0.7mm 304 0.7mm 304 stainless steel 0.7 mm 304 ext / 0.7 mm 304 stainless steel	0.7mm 304 0.7mm 304 stainless steel 0.7 mm 304 ext / 0.7 mm 304 stainless steel	0.7mm 304 0.7mm 304 stainless steel 0.7 mm 304 ext / 0.7 mm 304 stainless steel	0.7mm 304 0.7mm 304 stainless steel 0.7 mm 304 ext / 0.7 mm 304 stainless steel	0.7mm 304 0.7mm 304 stainless steel 0.7 mm 304 ext / 0.7 mm 304 stainless steel	0.7mm 304 0.7mm 304 stainless steel 0.7 mm 304 ext / 0.7 mm 304 stainless steel
Power Supply:	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
Power Input: Start Up Running Compressor HP	12 amps 2.5 amps 1/4	12 amps 2.5 amps 1/4	24 amps 4.2 amps 1/2	17 amps 3.5 amps 1/3	17 amps 3.5 amps 1/4	24 amps 4.3 amps 1/2
Energy Consumption:	3.2kW in 24hr	4.2kW in 24hr	10.2kW in 24hr	4.4kW in 24 hr	5.3kW in 24hr	11.4kW in 24h
Heat Rejection: (Evaporating at -10°C in 32°C ambient)	507 watts	665 watts	1223 watts	665 watts	665 watts	1223 watts
Refrigerant:	R134a	R134a	R404a	R134a	R134a	R404a
Defrost:	Automatic off- cycle	Automatic electric Door mullion heaters	Automatic electric Door mullion heaters	Automatic off-cycle	Automatic electric Door mullion heaters	Automatic electric Door mullion heaters
Insulation (max): ODP Zero Polyurethane	75mm	75mm	75mm	75mm	75mm	75mm
Noise Output:	dBA	dBA	dBA	dBA	dBA	dBA
Fittings: Shelves Trayslides	4 x 1/1GN (W530xD650) 16 pairs	4 x 1/1GN (W325xD530) 16 pairs	4 x 1/1GN (W325xD530) 16 pairs	6 x 1/1GN (W325xD530) 24 pairs	6 x 1/1GN (W325xD530) 24 pairs	6 x 1/1GN (W325xD530) 24 pairs

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams are committed to a policy continuing product development and innovation and as such, we reserve the right to change product specifications stated without prior notice.



Williams Refrigeration

Bryggen Road, North Lynn Industrial Estate King's Lynn, PE30 2HZ.
Tel: +44 (0)1553 817 000 Fax: +44 (0)1553 817 111 Spares: +44 (0)1553 817017
Website: www.williams-refrigeration.com e.mail: sales@williams-refrigeration.co.uk

